

SITE FENCING / CROWD BARRIER

WILLIAMSON CONSTRUCTION EQUIPMENT LIMITED

WEBSITE: www.wcelimited.co.uk
E-MAIL: hireandsales@wcelimited.co.uk

SITE FENCING **STRONG, EASY TO ERECT, COST EFFECTIVE, MAINTENANCE FREE, RE-USABLE**



ROUND TOP ANTI-CLIMB (GS7) SITE FENCING

The panel is constructed from heavy duty, anticlimb, galvanised steel mesh (2.5mm diameter) which is welded to a strong tubular frame that goes all the way round. The top corners of each panel are rounded, therefore reducing the amount of joints. Each panel is supplied with coupler and robust rubber footing.

This general-purpose system provides a means of temporary or semi-permanent protection to a wide range of applications such as building sites, car parks etc. Optional extras include anti-lift device and extension arms (see below).

Size	Weight	Wire Diameter	Mesh Type	Finish
3.5m Length x 2.0m High	20kg	2.5mm	Anti-Climb (GS7)	Galvanised



CROWD CONTROL BARRIER


A strong tubular frame houses solid steel bars for strength and durability, available and are generally supplied with tubular feet which are permanently welded to the frame.

We do stock a number of crowd control barriers without feet attached – these can be used in conjunction with anti-trip flat metal feet.




Size	Weight	Bar Diameter.	Finish
2.5m Length x 1.1m High	19kg	8mm	Galvanised

Crowd Control Barrier Fencing is not crush control barrier



RUBBER FOOT

(manufactured from solid thermo-plastic, it is very resilient to shock and therefore able to be used again and again)




FENCING COUPLER

(used singularly or in pairs for added security)



ANTI-LIFT DEVICE

(used in conjunction with a fencing coupler)



FENCING STABILISER

(ideal to give additional support to fence panels)

NEWCASTLE DEPOT (HEAD OFFICE)

UNIT 16, WESLEY DRIVE
BENTON SQUARE INDUSTRIAL ESTATE
NEWCASTLE UPON TYNE
NE12 9UP

TEL: 0191 - 215 0222
FAX: 0191 - 266 4859

CARLISLE DEPOT

ST NINIAN'S ROAD
UPPERBY
CARLISLE
CA2 4NE

TEL: 01228 - 514 814
FAX: 01228 - 599 815